






## PERFECT PATIO DOOR SYSTEM FEATURES AND BENEFITS

- All vinyl, multi-chamber profile design for superior insulating properties for your comfort and energy savings.
- Mechanically-joined frame with accessory groove in standard 5-5/8" frame depth.
- Mechanically fastened aluminum reinforced door panels for rigidity and strength.
- Standard sizes available: 5, 6 or 8' width by 6'8" or 8'0" height.
- AAMA certified zinc-plated, double tandem nylon rollers for durability and smooth, effortless sliding.
- Corrosion-resistant, anodized-aluminum tracks for ongoing, smooth gliding operation.
- Full perimeter triple layer weather stripping for excellent air and water tightness.
- Standard "landmark" handle with lock and key upgrade available.
- Heavy-duty screen with heavy-gauge extruded aluminum frame and fiberglass mesh for solid frame and smooth operation.
- Specially-designed fabrication equipment combined with some of the most efficient manufacturing processes ensure that the fit and functionality of a PERFECT© brand sliding Patio Door is of the highest quality.

## **ALSO AVAILABLE IN ENERGYSTAR VERSION 7**

CONFIGURATIONS XO AND OX 2 PANEL

**XO - LEFT SIDE ACTIVE** SLIDES RIGHT





**OX - RIGHT SIDE ACTIVE** 

SLIDES LEFT

EXTERIOR VIEW **Viewing Outside** 



5-5/8" Jamb


with deep

pockets

7/8" or 1" Low-E

ixed support

Argon glass



## MINI BLINDS



## **SPECIAL ORDER SIZES & OPTIONS**

2 PANEL OX AND XO: 5068 - 59 5/8" X 79 5/8" 5068 MICHIGAN

6068 - 71 5/8" X 79 5/8" 6068 MICHIGAN 70 5/8" X 79 5/8" 8068 - 95 5/8" X 79 5/8"

58 5/8" X 79 5/8"

can be quoted

3 or 4 Panel Configurations | Custom Painted Exterior Colors | Additional Handle Finishes



www.windowfactoryoutlet.com