



2 LIGHT SLIDER

200 & EnergyStar V7



Features

- **DOUBLE STRENGTH** insulated **LOW-E** with **ARGON GAS** glass sealed including **SUPER SPACER®** technology
- **SILL EXTENSION** with dual durometer for ease of installation
- **EXTRUDED** ½ screen with **BETTER VUE®** screening provides improved visibility, enhanced insect performance, air flow and light transmission
- **LIFT OUT SASH** for easy cleaning from the inside
- **INTERNAL ALUMINUM REINFORCEMENT**
- **FULLY WELDED FRAME & SASH**
- **BOTH SASHES SLIDE**
- **FULL INTERLOCK AT THE MEETING RAIL**
- Energy Efficient **FOAMED PROFILES**
- **DOUBLE LOCKS** included on heights of 27½" and over
- **3¼" FULLY WELDED FRAME**
- **UPGRADE to ENERGY STAR V7 with TRIPLE GLAZING**



Think about this:

The spacer system you choose is just as important as the window!
That's why we use:

Super Spacer®
SEALED



**LIFETIME
RESIDENTIAL
WARRANTY
GLASS BREAKAGE**

MANUFACTURING LIMITS

MANUFACTURING INCREMENTS - WIDTH AND HEIGHT EVERY ⅛" INCH

MINIMUM WIDTH 24⅞" MINIMUM HEIGHT 14⅝"

MAXIMUM WIDTH 76" MAXIMUM HEIGHT 64"

MAXIMUM WIDTH + HEIGHT = 128" UI

Window Options

EXTERIOR PAINTED COLORS (interior color is white or wood grain)




INTERIOR WOOD GRAIN COLORS (wood grain color choices - natural oak or cherry)

NATURAL OAK

CHERRY

STANDARD STRENGTH TRIPLE PANE OR DOUBLE STRENGTH TRIPLE PANE

Two panes
(standard strength or double strength)
of Low-E glass and
one pane of clear glass with
argon gas in both chambers



Privacy Plus Performance OBSCURED GLASS



TEMPERED GLASS




Grids are installed between the glass panes during manufacturing for easy cleaning

**GRIDS
PATTERNS
AVAILABLE**



CONTOUR GRIDS



FLAT GRIDS